


PIN	ø1.65	ø2.0	ø2.35	ø2.5
APPD.				

SCHMATIC



SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 0.03\Omega$;
3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. Life test: 5,000 cycles.

6	COVER	1	PBT/PA66	
5	HOUSING	1	PBT/PA66	
4	FLAT PIECE	1	H62 BRASS	Ag(Sn)-Plating
3	SPRING	1	BRONZE/65Mn STEEL	Ag(Sn)-Plating
2	CURVE PIECE	1	H62 BRASS	Ag(Sn)-Plating
1	PIN	1	H59 BRASS	Ni-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

UNIT: MM	TYPE:	MODEL NO:	PAPER NO:	PAGE 1 OF 1
	DC JACK	DC-005B	A4	
			TOLERANCE	ANGLES
			±0.15	±1.5'
			SCALE	VER
			3:1	1

DESIGNER		深圳市亿利百斯特电子有限公司
CHECK		
APPROVED		