


SCHMATIC



PIN	φ2.0	φ2.5	
APPD.			

- SPECIFICATION**
1. Rating : DC 30V 0.5A;
 2. Contact resistance: $\leq 0.03\Omega$;
 3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
 4. Withstand voltage: 500VAC ;
 5. Insertion and extraction force: 3-20N;
 6. life test: 5,000 cycles.

5	PIN	1	H59 BRASS	Ni-Plating
4	HOUSING	1	PA66	
3	CURVE PIECE	1	H62 BRASS	Cu-Sn-Plating
2	FLAT PIECE	1	H62 BRASS	Cu-Sn-Plating
1	SPRING	1	65Mn STEEL	Cu-Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

UNIT: MM	TYPE:	MODEL NO:	PAPER NO:	PAGE 1 OF 1
	DC JACK	DC-004	A4 TOLERANCE ANGLES SCALE VER	
			±0.15 ±1.5' 4:1 1	

DESIGNER		深圳市亿利百斯特电子有限公司 亿利百斯特 ShenZhen ElyBest Electronics Co., Ltd
CHECK		
APPROVED		