

承 認 書

APPROVE SHEET



敬請承認如下之形式規格書：

客 戶 名 稱

CUSTOMER:

貴公司製品名

CUSTOMER PN:

本公司製品名：

PRODUCT PN:

轻触开关

貴公司規格

APPROVAL DAT:

本公司規格：

PRODUCT CODE:

EL-40A06011B两档

客戶料號：

CUSTOMER NO.:

本公司規格書編號：

PRODUCT DRAWING NO.:

新品承認
NEW APPROVE

APPROVAL

CHECK

DESIGN

規格變更再承認
CHANGE CODE APPROVE
AGAIN

批 准

審 查

設 計

朱艳军

彭佳伟

王园

材料變更再承認
CHANGE MATERIAL APPROVE
AGAIN

DATE:

DATE:

DATE:

貴公司承認欄

APPROVAL SIGNATURES

請於____年____月____日前承認返回
PLEASE RETURN TO ADMIT XUNIANRUI

日期 DATE:_____

深圳市亿利百斯特电子有限公司

ShenZhen ElyBest Electronics Co ., Ltd

付文鹏 (Vincent Fu)

Tel : 0755-28213003

Fax: 0755-85215085

Mob:18923844556

Email : vincent@elybest.com

Add : 深圳市龙岗区平湖街道竹高塘路88号旭美智创园2栋2楼

规 格 承 认 书				规格书编号 20211009
品 名	DOUBLE TACT SWITCH	型 号	EL-40A060IIB	1/10
1. General Specification 基本说明				
1.1 Scope 范围 This specification covers the requirements for single key switches which have no Key top(DOUBLE TACT SWITCHES:MECHANICAL CONTACT).此规范含盖单推柄和无推柄的轻触开关要求				
1.2 Operating Temperature Range 使用温度范围 -40 to +85°C(normal humidity, normal press.) 正常湿度，标准压力				
1.3 Storage Temperature Range 保存温度范围 -40 to +85°C(normal humidity, normal press.)				
1.4 Test Conditions 测试条件 Tests and measurements shall be made in the following standard conditions unless otherwise specified: 测试和计量按下列标准条件除非特殊说明 Normal temperature (temperature 5 to 35°C) 标准温度 Normal humidity (relative humidity 45 to 85%) 正常湿气 Normal pressure (pressure 860 to 1060 mbars) 标准压力 In case any question arises from the judgment made, tests shall be conducted in the following conditions: Temperature (20±2°C) 温度 Relative humidity (65±5%) 相对湿度 Pressure (860 to 1060 mbars) 压力				
2. Type Of Actuation 动作类型				
Tactile feedback 轻触返回				
3. Contact Arrangement 1 poles 1 throws 接触形式 1 接点 1 回路 (Details of contact arrangement are given in the assembly drawings.) 细接点形式在装配图中				
4. Maximum Ratings DC 12 V 50 mA 最大额定值 DC 1 V 10 μA 最小额定值				

规格承认书		规格书编号 20211009	
品名	DOUBLE TACT SWITCH	型号	EL-40A060IIB
5. 外形、结构:		5.1 外形图:	
<p>REFERENCE DRAWING</p> <p>CIRCUIT DIAGRAM 1st</p> <p>CIRCUIT DIAGRAM 2st</p> <p>P. C. B LAND DIMENSION</p> <p>SPECIFICATION</p> <ol style="list-style-type: none"> Rating: DC 12V 50mA Max Contact resistance: 100mΩ MAX Insulation resistance: 100MΩ Min Dielectric strength: 250VAC/min Operating force: 1st 500gf 2st 550gf Travel: 1st 0.7mm 2st 0.55mm Operating life: 10,000 cycles <p>GDEL 深圳市亿利百斯特电子有限公司</p>			

规 格 承 认 书

规格书编号

20211009

品 名


DOUBLE TACT SWITCH

型 号

EL-40A060IIB

3/10

5.2 构造:





序号	零部件名称	数量	材料名称	表面处理	备注
1	TERMINAL	1	BRASS	Ag plating	
2	BASE	1	PA6T		
3	INNER CONTACT	2	SUS 301	Ag plating	
4	CONTACT	2	SUS 301	Ag plating	
5	INNER STEM	1	RUBBER		
6	COVER	1	SUS 301		
7	STEM	1	PA6T		

规格承认书				规格书编号 20211009
品名	DOUBLE TACT SWITCH	型号	EL-40A060IIB	4/10
6. General Specification 性能				
6.1 电气的性能				
Item 项目	Test Condition 测试条件		Requirements 要求	
6.1.1 Contact Resistance 接触电阻	<p>Applying static load twice the actuating force to the center of the stem, measurements shall be made with a 1 kHz small-current contact resistance meter.</p> <p>用两倍的动作力作静负载施加于按钮的中心,并用 1 千赫小电流接触电阻仪测量</p>		100mΩ 以下	
6.1.2 Insulation Resistance 绝缘电阻	<p>Measurements shall be made following application of DC100V potential between terminals and between individual terminals and frame for one minute. 在端子与端子之间,端子与外壳之间施加 DC100V, 一分钟</p>		100MΩ 以上	
6.1.3 Dielectric Withstanding Voltage 电气耐压	<p>AC250V(50Hz or 60Hz) shall be applied between terminals and between individual terminals and frame for one minute. 在端子与端子之间,端子与外壳之间施加 AC250V(50HZ-60HZ)</p>		<p>There shall be no breakdown. 无击穿、闪烁现象</p>	
6.1.4 Bounce 抖动	<p>Lightly striking the center of the stem at a rate encountered in normal use (3 to 4 operations per sec),</p> <p>Bounce shall be tested when "ON" and "OFF".</p> <p>在正常使用中(以每秒 3-4 次周期)轻轻地在手柄中心加力,在通与断瞬间测试抖动</p> <p>Switch</p> <p>DC3-5V</p> <p>5k Ω</p> <p>Oscillograph 示波器</p> <p>t 为触点抖动时间</p>		10mS 以下	

规格承认书				规格书编号 20211009
品名	DOUBLE TACT SWITCH	型号	EL-40A060IIB	5/10
6.2 机械的性能				
Item 项目		Test Condition 测试条件		Requirements 要求
6.2.1	Actuating Force 动作力	Place the switch such that the direction of switch operation is vertical and then gradually increase the load applied to the center and around of the stem, the maximum load required for the stem to come to a stop shall be measured. 开关的动作方向为垂直放置开关向推柄中心及左右逐渐地增加负荷直到推柄停止时所测量的最大负荷		第一段 1st: <u>500</u> ± <u>100</u> gf 第二段 2st: <u>600</u> ± <u>100</u> gf
6.2.2	Travel 行程	Place the switch such that the direction of switch operation is vertical and then apply a static load twice the actuating force to the center and around of the stem, the travel distance for the stem to come to a stop shall be measured. 开关的动作方向为垂直放置开关,并以双倍动作力的静负荷作用推柄中心及左右,测量推柄从开始到停止的行程距离		第一段 1st: <u>0.70</u> ± <u>0.30</u> mm 第二段 2st: <u>0.55</u> ± <u>0.30</u> mm
6.2.3	Return Force 返回力	The sample switch is installed such that the direction of switch operation is vertical and, upon depression of the stem in its center the whole travel distance , the force of the stem to return to its free position shall be measured. 开关的动作方向为垂直放置开关,在已有行程的推柄中心向上减小压力,推柄回到自由位置时所测量到的力		<u>60</u> gf min
6.2.4	Static Strength 静止强度	Placing the switch such that the direction of switch operation is vertical, a static load of <u>3</u> kgf shall be applied in the direction of stem operation for a period of <u>60</u> seconds. 开关的动作方向为垂直放置开关,在推柄动作方向施加 3KG 的静负荷, 60 秒时间		There shall be no sign of damage mechanically and electrically. 无机械的和电气的损伤迹象

规 格 承 认 书				规格书编号 20211009
品 名	DOUBLE TACT SWITCH	型 号	EL-40A060IIB	6/10
6.3 使用耐久性能				
Item 项目		Test Condition 测试条件		Requirements 要求
6.3.1	Operating Life 动作寿命	<p>Measurements shall be made following the test set forth below: 按下列条件进行寿命试验</p> <p>(1)DC 5V 5mA resistive load. DC 5V 5mA 阻性负载</p> <p>(2)Rate of operation: 2 to 3 operations per second 动作频率: 2-3 次/每秒</p> <p>(3)Depression: <u>825</u> gf 减压力</p> <p>(4)Cycles of operation: 1×10^4 cycles 动作次数: 1×10^4 次</p>		Contact resistance: <u>200</u> mΩ Max. 接触电阻 Insulation resistance : <u>50</u> MΩ Min. 绝缘电阻 Actuating force: 动作力 + <u>30</u> % or - <u>30</u> % of initial force. ±30% 初始动作力 Item 6.1.3 Item 6.2.2
6.3.2	Moisture Resistance 耐潮湿	<p>Following the test set forth below the sample shall be left in normal temperature and humidity conditions for one hour before measurements are made: 样品按下列条件进行耐潮湿试验, 试验后在正常温度和湿度条件下放置 1 小时后测定</p> <p>(1) Temperature: $60 \pm 2^\circ\text{C}$ 温度</p> <p>(2) Relative humidity: 90 to 95% 相对湿度</p> <p>(3) Time: 96 hours 时间</p> <p>Water drops shall be removed. 擦除水珠</p>		Contact resistance: <u>200</u> mΩ Max. 接触电阻 Insulation resistance : <u>50</u> MΩ Min. 绝缘电阻 Item 6.1.3、6.1.4 Item 6.2.1~6.2.3
6.3.3	Low Temperature Resistance 耐低温	<p>Following the test set forth below the sample shall be left in normal temperature and humidity conditions for one hour before measurements are made: 样品按下列条件进行耐低温试验, 试验后在正常温度和湿度条件下放置 1 小时后测定</p> <p>(1)Temperature: $-40 \pm 2^\circ\text{C}$ 温度</p> <p>(2) Time: 96 hours 时间</p> <p>Water drops shall be removed. 擦除水珠</p>		Contact resistance: <u>200</u> mΩ Max. 接触电阻 Insulation resistance : <u>50</u> MΩ Min. 绝缘电阻 Item 6.1.3、6.1.4 Item 6.2.1~6.2.3
6.3.4	Heat Resistance 耐热	<p>Following the test set forth below the sample shall be left in normal temperature and humidity conditions for one hour before measurements are made: 样品按下列条件进行耐热试验, 试验后在正常温度和湿度条件下放置 1 小时后测定</p> <p>(1)Temperature: $85 \pm 2^\circ\text{C}$ 温度</p> <p>(2) Time: 96 hours 时间</p>		Contact resistance: <u>200</u> mΩ Max. 接触电阻 Insulation resistance : <u>50</u> MΩ Min. 绝缘电阻 Item 6.1.3、6.1.4 Item 6.2.1~6.2.3

规格承认书				规格书编号 20211009
品名	DOUBLE TACT SWITCH	型号	EL-40A060IIB	7/10
Item 项目	Test Condition 测试条件			Requirements 要求
6.3.5	Change of Temperature 温度循环	<p>Following ten cycles of high temperature test .The Sample shall be Placed in Normal temperature and humidity Conditions for one hour before measurements are made. During this test, water drops shall be removed.</p> <p>样品按下列条件进行高低温循环试验,试验后在正常温度和湿度条件下放置 1 小时后测定</p> <p>A: +85±2°C B: -40±2°C C: 2 小时 D: 1 小时 E: 2 小时 F: 1 小时</p> <p>Cycling: Five cycles 周期: 5 次</p>		<p>Contact resistance: <u>200</u> mΩ Max. 接触电阻 Insulation resistance : <u>50</u> MΩ Min. 绝缘电阻 Item 6.1.3、6.1.4 Item 6.2.1~6.2.3</p>
6.3.6	Salt Spray Test 盐雾试验	<p>The salt spray test shall be conducted at the following conditions : 样品按下列条件进行盐雾试验</p> <p>(1)Density(浓度): 溶液($5 \pm 1\%$) NaCl (质量百分比) (2)Temperature: $35 \pm 2^\circ\text{C}$ 温度 (3) Time: 24hours 时间</p>		金属件无发黄、生锈
6.3.7	Vibration Resistance 耐振动	<p>Measurements shall be made following the test set forth below: 按下列条件进行抗振动试验</p> <p>(1)Range of oscillation: 10 to 55Hz 频率范围 (2)Amplitude,pk-to-pk:1.5mm 振幅:峰-峰 1.5mm (3)Cycle of sweep: 10-55-10Hz in one minute, approx. 扫描周期: 10-55-10Hz 约一分钟内 (4)Mode of sweep: Logarithmically sweep or uniform sweep. 扫描方式: 对数扫描式恒定扫描 (5)Direction of oscillation: 振动方向 Three mutually perpendicular directions, including the direction of stem travel. 3 个相互垂直方向,包括推柄行程方向 (6)2 hours each ,for a total of 6hours. 每方向 2 小时,共 6 小时</p>	<p>Item 6.1 Item 6.2.1、6.2.2</p>	

规格承认书				规格书编号 20211009			
品名	DOUBLE TACT SWITCH	型号	EL-40A060IIB	8/10			
Item 项目	Test Condition 测试条件		Requirements 要求				
6.3.8	Impact Shock Resistance 抗冲击	<p>Measurements shall be made following the test set forth below: 按下列条件进行冲击试验</p> <p>(1)Acceleration: 80g 加速度</p> <p>(2)Cycles of test : 3 cycles each in 6directions, for a total of 18cycles 试验次数: 每个方向 3 次, 6 个方向共 18 次</p> 	<p>Item 6.1</p> <p>Item 6. 2.1、6.2.2</p>				
7. 焊接条件:							
Item 项目	Recommended conditions 推荐条件						
7.1	Hand Soldering 手工焊接	<p>Please practice according to bellow conditions:</p> <p>(1)Soldering temperature :$\leq 260^{\circ}\text{C}$</p> <p>(2)Continuous soldering time:$\leq 5\text{ S}$</p> <p>(3)Capacity of soldering iron:$\leq 20\text{ W}$</p> <p>请按以下条件进行焊接:</p> <p>(1)焊锡温度: $\leq 260^{\circ}\text{C}$</p> <p>(2)连续焊接时间: $\leq 5\text{ S}$</p> <p>(3)电铬铁的功率: $\leq 20\text{ W}$</p>					
7.2	Automatic Flow Soldering 自动焊接	<p>For the product of SMT ,type solder according to the following conditions</p> <p>对于 SMT 产品, 请按以下条件进行焊接</p> <p>surface of product temperature 部品表面温度 (°C)</p>  <p>peak temperature 260°C max. 3sec max.</p> <p>time inside soldering equipment 炉内通过时间</p> <p>Caution: the condition mentioned above is a temperature on the PWB surface on which parts are mounted. There are cases where PWB temperature greatly differs from switch's surface temperature depending on PWB material, size, thickness, etc. The switch's surface temperature shall not allowed to exceed 260°C 注意: 以上提及的条件是零部件上 PWB 表面的温度, 由于 PWB 的材料、尺寸、厚度等不同, PWB 从开关表面获得的温度也会有很大差异, 因此, 千万小心不要让开关表面温度超过 260°C</p>					

规 格 承 认 书				规格书编号 20211009
品 名	DOUBLE TACT SWITCH	型 号	EL-40A060IIB	9/10

8. Other Precautions 其他注意事项:

- (1) Following the soldering process, do not try to clean the switch with a solvent or the like.
进行焊接过程中，不可以用溶剂或类似品清洗开关
- (2) Safeguard the switch assembly against flux penetration from its topside.
防止助焊剂从开关的顶端渗入
- (3) Please have the products keep in close status and the storage time is 90 days guaranty after delivering the goods at most.
交货后保证开关处于封密状态并库存时间 90 天以下

9. Reel Packaging 盘装

9.1 Scope 范围

This specification covers the requirements of the reel packaging for SMT standard type of DOUBLE TACT SWITCHes. 该规范包含 SMT 标准型拨动开关的绕带封装的要求

9.2 Packaging Materials 封装材料

Item 项目	Description 说 明
Package 包 装	Cartons 卡通箱
Reel 转 轴	Delete Cartons 可降解箱
Carrier Tape 载 带	Polypropylene 聚丙烯